



**COMET SYSTEM, s.r.o.**

1.maje 1220

756 61 Roznov pod Radhostem

CZECH REPUBLIC

Tel.: +420 571 653 990

E-mail: [info@cometsystem.com](mailto:info@cometsystem.com)

## T-PRINT G0221E temperature recorder with printer



code: G0221E

Complete solution for temperature record during the transport.

The device **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

- print-out of temperature record during transport of food, pharmaceuticals, flowers, live animals and other goods
- designed especially for installation in driver's cabin
- easy installation

### Features

#### Advantages of Dataloggers:

- record from one or two temperature probes
- delivery Ticket, Journey Ticket and Multi Day printouts
- selectable numerical and graphical print-out
- print from the last record to the history till button is pressed
- print up to set hour in current day
- print of set number of hours to the history
- fast print to usual 57mm thermo paper in 10m rolls
- large graphic illuminated display
- indication of temperature exceeding by LED and acoustically
- approximately 3400 record lines/one paper roll
- record of actual or average values
- calculated MKT - mean kinetic temperature for storing of pharmaceuticals in the PC program
- cyclic record - after filling the memory oldest records are overwritten by new
- no need to download data - large 1MB memory stores up to 5 years of record permanently in memory
- USB interface for record download to the PC
- free PC software
- fifteen selectable languages, e.g. English, German, French, Italian, Polish, Dutch, Spanish, Portuguese, Romanian, Czech
- degrees of Celsius and Fahrenheit
- included traceable calibration certificate
- TÜV SÜD certified to conform to EN 12830, Class 1 and EN 13486, Class 1 for the transport of food

#### Included in delivery:

- Traceable calibration certificate with declared metrological traceability of etalons is based on requirements of EN ISO/IEC 17025 standard
- Quick start manual

- Free basic Windows software is ready to download at folder [Download](#)

## Technical Data

Technical parameters	Value
Measured Value	Temperature
Construction Type	For External Temperature Probes Pt1000
Temperature Measuring Range	-90 to 260 °C
Two-State Input	No
Lcd Display	Yes
Built-In Printer	Yes
Operating temperature range	-30 to +65°C
Accuracy of temperature input without probe	±0.2°C
Resolution of the reading	0.1°C
Real time clock	year, leap year, month, day, hour, minute, second
Data logging interval	adjustable from 1 minute to 60 minutes
Total memory capacity	1MB - up to 172 000 records
Dimensions	175 x 124 x 51mm (W x H x D)
Power	9 to 32 V dc, protected against alternator load shedding + internal Lithium battery
Consumption while printing	approximately 8 W
Consumption - not printing	approximately 0.1 W
IP protection	IP20
Weight without probes	approximately 700g
Warranty	3 years