



## Model: AE2415Z-FZ1B (AE2415Z-FZ)

### Product Description

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 220-240V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	220V ~ 50HZ	1300	328	381	307	4.23	1.07	1.24	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)
ASHRAE (R-452A)	220V ~ 50HZ	1151	290	337	286	4.03	1.01	1.17	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)
ASHRAE (R-449A)	220V ~ 50HZ	1084	273	318	268	4.04	1.02	1.19	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

#### General

**Evaporating Temp. Range:** -40°C to -10°C (-40°F to 14°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 10  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 7.33  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 285

#### Electrical

**Voltage Range (50 Hz):** 198-253  
**Voltage Range (60 Hz):** N/A  
**Locked Rotor Amps (LRA):** 12.5  
**Rated Load Amps (RLA 50 Hz):** 1.9  
**Rated Load Amps (RLA 60 Hz):** 0  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** 9.3  
**Motor Resistance (Ohm) - Start:** 15.82  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

**CCC Listed, CE Listed, GOST RUSSIA Listed, GOST  
UKRAINE Listed, IRAM Listed, VDE Listed**